STAND ALONE CAMERA SYSTEM





PRODUCT DATA SHEET

DESCRIPTION

This is an all-in-one security camera system that can work on many different platforms and handle a multitude of different situations, to include but not limited to, concerts, sports events, protests, etc... With a 48-hour battery life, the lithium ion batteries will keep your system going for days. The camera system(s) contains 3 parts:

1. Lockable Power/Technology Pack(s)

The power/technology pack(s) contains all the batteries, and technology that the system requires to work. It can be secured with two locks. The power pack(s) has just one power switch to turn on and operate the entire system. The power pack(s) also has a voltmeter, charging port and ethernet connection for the camera(s) on the outside of the box. The system(s) can be placed



on the ground, a balcony, or any other level surface. The system(s) can even attach to a tree or telephone pole for an even higher view of the surrounding area.

The technology in this system allows for you to view the system anywhere you are in the world, providing you have an active internet connection. The system will run off cellular data or currently installed internet connection from your home or business. Setup is quick, simple and can be up and running in under 5 mins. You can use cellular plans from Verizon, AT&T or T-Mobile, depending on your coverage area in the location in which you place the system.

2. Expandable Telescoping Locking Pole(s)

The Expandable Telescoping Locking Pole(s) allows you to expand your system from 62 inches high (Minimum) to 80 inches high (Maximum) and everywhere in between. The pole(s) is made of high-grade aluminum, so that it helps to keep the overall weight to a minimum.

u can use cellular plans from Verizon, AT&T or T-Mobile, depending on your coverage area in the location in which you place the system.



3. The Camera(s)

Has the ability to integrate with your existing camera systems.

The camera(s) is a Pan-Tilt-Zoom (PTZ) camera(s). The PTZ can be moved up and down, left, and right and/or zoomed in and out optically (4x) and digitally (16x). The camera(s) works with a temperature variation from -22oF (-30oC) to 140oF (60oC). The camera(s) has an IP66 rating (rated as dust tight and protected against heavy seas or powerful jets of water.).





ClearView Asset Protection, LLC

128 Green Valley Road, Hughesville, PA 17737

1-888-461-7121